

Generador Silencioso - Bencina

1. Generador a Bencina
Cantidad: 4 unidades



Model		FG2000is
Engine	Type	Forced Air-Cooled, 1-Cylinder, 4-Stroke, OHV
	Displacement	79.7 cc
	Rated power output	2.3 KW
	Max. power output	2.5 KW
	Bore*Stroke(mm)	48.6x43.0
	Ignition system	C.D.I
	Starting system	Recoil starting
	Fuel tank capacity	4.0 L
	Fuel consumption	400 g/KW*h
	Continous operating (70% of rated load)	6 h
	Noise (7m away)	58 dba
Generator	Rated output frequency	60/50 HZ
	Rated A.C. Output	110/220V
	D. C. Output	12 V, 8.3 A
	Rated power output(KVA)	1.6 KW
	Max. power output(KVA)	2.0 KVA
Dimensions	Length*Width*Height	480*285*390 mm
	Net weight / Gross weight	21.5/23.5 kg
	Packing size(mm)	520*330*460 mm
Features	Fuel gauge	Y
	Auto voltage adjustor	Y
	Low oil alert	Y
	Circuit protector	Y
	Parallel connection capability	Y
	Quantity	4
	Certificates	CE, GS, Euro II, ETL, EPA, CARB, Noise level