

HG3500E



Cantidad : 2

Bencina y Gas
No silencioso

| | | |
|---|--|---------|
| Model | HG3500E | |
| Rated frequency (Hz) | 50 | 60 |
| Rated output (kVA) | 2.5 | 2.7 |
| Max. output (kVA) | 2.7 | 3 |
| Rated Voltage (V) | 115/230 | 120/240 |
| Rated rotation speed (r/min) | 3000 | 3600 |
| Phase NO. | Single phase | |
| Power factor (Cos Φ) | 1 | |
| Insulation Grade | B | |
| Pole number | 2 | |
| Excitation mode | Self-excitation & constant voltage (AVR) | |
| Panel Type | General Panel | |
| Voltage (V) | 115/230 | 120/240 |
| Receptacle | Two receptacles | |
| Connection pole | Without | |
| DC12V output | Connection pole output | |
| Overall dimen (L×W×H) (mm) | 590×445×450 | |
| Dry weight(kg) | 52 | |
| Working assorting weight (Kg) | | |
| Noise level (7m) dB(A) | 66 | |
| Structure type | Open frame | |

| | | |
|--|--|----------|
| Engine Model | FG168FGE | |
| Engine Type | Single cylinder, air-cooled, four- stroke, OHV | |
| Cylinder NO.-bore×stroke (mm) | 1-68×54 | |
| Displacement (ml) | 196 | |
| Rated power [KW/(r/min)] | 3.6/3000 | 4.0/3600 |
| Compression ratio | 8.5:1 | |
| Rated rotation speed (r/min) | 3000 | 3600 |
| Combustion system | T.C.I | |
| Cooling system | Air cooled | |
| Lubrication system | Splashed | |
| Starting system | Recoil starter or electric starter | |
| Fuel type | Automatic unleaded gasoline | |
| Lube oil brand | CD grade or SAE10W-30, 15W-40 | |
| Capacity of cooling water (L) | N/A | |
| Lube capacity (L) | 0,6 | |
| Starting motor capacity (V-kW) | 12V 0.4kW | |
| Charging generator capacity (V-A) | 12V 8A | |
| Battery capacity (V-Ah) | 7Ah/12V | |
| Fuel consumption (g/kW.h) | ≤395 | |
| Fuel tank capacity (L) | 13,5 | |
| Continuous running time (hr) | 9 | 9 |